

2019-R25
EXHIBIT 'A'



Kenworth of Richfield
2890 Brecksville Rd
Richfield, OH 44286
Ph: 330-659-4123
Fax: 330-659-4481
Toll Free: 800-362-7490

2020 Kenworth T370 Plow Truck Chassis
City of Green Sourcewell Member #43084

We are pleased to quote you on your new 2020 T370 Snow Plow Chassis purchase
Please see attached specifications for your review and consideration

The sale price for the 2020 Kenworth T370 Cab and Chassis

Sourcewell Contract #081716-KTC Price per attached specs for single axle \$83,997.00

For Front Frame Extension (If Body Company Requests) ADD \$780.00

5 year 100,000 mile
Engine and engine after treatment ADD \$2,290.00

Please call me on my cell with any questions

Thanks,
Ray Gindlesperger
Kenworth of Richfield
2890 Brecksville Rd.
Richfield, Ohio 44266
330-659-4123
330-523-6493 cell no.

FRANCHISED DEALER OF KENWORTH TRUCKS AND SUBSIDIARY OF THE HISSONG GROUP FAMILY OF COMPANIES

KENWORTH OF RICHFIELD / KENWORTH OF CANTON / KENWORTH OF COLUMBUS
KENWORTH OF ASHLAND / KENWORTH OF CHILLICOTHE / BROKERS INVESTMENT CORP.



Kenworth of Richfield H200
2890 Brecksville Rd

City of Green
5383 Massillon Rd.

Richfield, Ohio United States 44286
Phone:
Fax:
Email:

Green, Ohio United States 44232
Phone: (330) 896-5503
Fax:
Contact Email:
Prepared for:

Vehicle Summary

Unit		Chassis	
Model:	T370 SERIES	Fr Axle Load (lbs):	16000
Type:	CONVENTIONAL	Rr Axle Load (lbs)	23000
Description:	FULL TRUCK	G.C.W. (lbs):	39001
	GREEN	Road Conditions:	
Application			
Intended Serv.:	Snowplow. Vehicles which are configured for	Class A (Highway)	85
Commodity:	Gravel/crushed rock/sand	Class B (Hwy/Mtn)	10
		Class C (Off-Hwy)	05
		Class D (Off-Road)	00
Body			
Type:	End dump	Maximum Grade:	6
Length (ft):	10.0	Wheelbase (in):	153
Height (ft):	12.0	Overhang (in):	50
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):	68
		Cab to Axle (in):	85
		Cab to EOF (in):	135
Trailer		Overall Comb. Length (in):	243
No. of Trailer Axles:	0		
Type:		Special Req.	
Length (ft):	0.0	U.S. Domestic Registry, 50-State	
Height (ft):	0.0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	120		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 3/5/2019 11:01:32 AM
Effective Date: Jan 1, 2018
Prepared by: Administrator

Complete

Model Number: T370 SERIES CONVENTIONAL
Quote/DTPO/CO: Q70120068
Version Number: 41.20



Kenworth of Richfield H200
2890 Brecksville Rd

City of Green
5383 Massillon Rd.

Richfield, Ohio United States 44286
Phone:
Fax:
Email:

Green, Ohio United States 44232
Phone: (330) 896-5503
Fax:
Contact Email:
Prepared for:

Data	Code	Description	Weight
Model			
0000370	O	T370 SERIES CONVENTIONAL Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floor mat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	9,642
0070006	O	T370 Class 7: medium-duty Conventional.	0
0080050	O	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
0090015	O	Medium-duty 4x2 automatic.	0
0091042	O	Gravel/crushed rock/sand	0
0093025	O	Snowplow. Vehicles which are configured for mounting a snowplow to the front. May also have dump or other body. Typically includes some operation off of paved roads. Road usage: majority of Class A & B, do not code for Class D.	0
0095010	O	End dump	0
0098025	O	U.S. Domestic Registry, 50-State	0

Engine & Equipment

0129532	O	PACCAR PX-9 330 2017 330@2000 320@2200 1000@1400 Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. N09200 N205 75...Standard Maximum Speed Limit [LSL] N09220 N207 0...Expiration Distance N09260 P14 66...Maximum Accelerator Pedal Vehicle Speed N09300 P19 66...Maximum Cruise Speed N09360 N203 252...Reserve Speed Function Reset Distance N09380 N202 0...Maximum Cycle Distance N09400 N206 10...Maximum Active Distance N09420 N201 0...Reserve Speed Limit Offset N09440 P11 NO...Engine Protection Shutdown N09460 P06 NO...Gear Down Protection N09480 P26 1400...Max PTO Speed N09500 P02 NO...Cruise Control Auto Resume N09520 P04 NO...Auto Engine Brake in Cruise	555
---------	---	---	-----

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 3/5/2019 11:01:32 AM
Effective Date: Jan 1, 2018
Prepared by: Administrator

Complete

Model Number: T370 SERIES CONVENTIONAL
Quote/DTPO/CO: Q70120068
Version Number: 41.20



Data	Code	Description	Weight
		N09540 N209 0...Expiration Distance	
		N09560 P520 YES..Enable Idle Shutdown Park Brake Set	
		N09580 P32 5....Timer Setting	
		N09600 P233 YES..Enable Impending Shutdown Warning	
		N09620 P234 60...Timer For Impending Shutdown Warning	
		N09640 P516 35...Engine Load Threshold	
		N09680 P33 NO...Idle Shutdown Manual Override	
		N09720 P230 YES..Enable Hot Ambient Automatic Override	
		N09740 P46 40...Low Ambient Temperature Threshold	
		N09760 P56 60...Intermediate Ambient Temperature Threshold	
		N09780 P47 80...High Ambient Temperature Threshold	
1000158	O	Prospector Version 43.0 Replaces 42.1	0
1000684	O	Effective VSL Setting NA	0
1000858	O	Engine Idle Shutdown Timer Disabled	0
1000859	O	Enable EIST Ambient Temp Override	0
1000891	O	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	0
1002060	S	Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0
1031130	S	Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.	0
1105230	O	Fan Hub: Horton 2-Speed for ISL9, ISL-G, PX-8 or PX-9	0
1121200	S	Cooling module: 1000 square inches T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	0
1247194	O	Exhaust:2017 EPA RH Under Cab DPf/SCR For PX-9 w/ Single Vertical RH Side of Cab Tailpipe.	215
1290124	O	Tailpipe: 5 in. single 24 in. 45 degree curved.	-2
1321145	O	Fuel Filter:Fleetguard FS1003 Fuel/Water Separator for PX-9	0
1321200	O	Run Aid:None *For Fuel Filter	0
1321305	O	Start Aid:12V Heat *For Fuel Filter	1
1816260	S	Alternator: PACCAR 160 amp, brush type	0
1821210	O	Batteries: 3 PACCAR GP31 threaded post (700-730) 2100-2190 CCA dual purpose.	57
1836100	S	Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
1900082	O	Multi-function engine connector for body builder interface for Cummins.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/5/2019 11:01:32 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q70120068
Prepared by:	Administrator		Version Number:	41.20



Data	Code	Description	Weight
Transmission & Clutch			
2011205	O	Transmission: Allison 3000RDS 6-speed w/PTO drive gear. 5th Gen controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions. Requires a push button shift control code. Oil temperature gauge is standard on class 8 models.	291
2406452	O	Driveline: 2 SPL170XL 1 centerbearing requires 3500057 interaxle driveline.	70
2409916	O	One bolted centerbearing crossmember. This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	11
2410018	O	Torque converter included w/Allison Transmission.	0
2410204	O	Delete Allison Fuel Sense	0
2410426	U	Allison 5th Gen RDS PKG 223 for 3000,	0
2429358	O	Rear transmission support springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	0
Front Axle & Equipment			
2504160	O	Dana Spicer D1600 Front Axle 16K standard track.	120
2603006	S	Front brakes included w/ front hub package.	0
2703016	O	Front Brake:Bendix 16.5x6 air brake package for 16K non-driving front axle. Includes cast drums, iron 10-bolt hub pilot Preset hubs, hub caps, oil seals & slack adjusters. For use with 22.5 inch wheels	75
2864026	O	Front Springs Taperleaf 16K 2-stage with shocks and 54 in. spring length. T370 w/16K front axle.	172
2895300	O	Dual power steering gears: 16K.	77
2899336	O	Power Steering Cooler:Radiator Mounted Air-to-Oil	11
Rear Axle & Equipment			
3041190	O	Single Dana Spicer S23-190 single reduction rear axle. Single rear axle rated at 23K.	255
3200614	O	Rear Axle Ratio - 6.14.	0
3300000	S	Single rear brakes included w/rear hub package.	0
3401001	S	23K air brake package includes 16-1/2x7 in. brakes, cast drums, aluminum 10-bolt hub pilot Preset hubs, automatic slack adjusters and oil seals for use w/ 22.5 in. wheels.	0
3485009	S	Spring Brake: 3030 high output single.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/5/2019 11:01:32 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q70120068
Prepared by:	Administrator		Version Number:	41.20



Data	Code	Description	Weight
3490047	O	Dustshields for drum brakes: all rear axles.	11
3495226	S	Bendix 4S/4M anti-lock brake system.	0
3531001	O	Wheel Differential Lock for Dana Spicer Axles S21-170/172, S21-190, S23-170/172, S23-190, S26-190 & S30-190; adds D to the end of the axle part number.	28
3636430	O	Rear suspension: single Reyco 79KB taperleaf 23K with helper spring. Medium-duty. Unladen Height: 11.4 in. Laden Height: 9.7 in. Not available with rear air disc brakes.	57
3836315	O	Bolted rear suspension crossmembers for Reyco 79KB. Replaces T3 standard.	41
Tires & Wheels			
4038677	O	Front tires: Goodyear G291 315/80R22.5 18PR. 42.3 in. diameter, all position. 19.7 in. SLR.	154
4238682	O	Rear tires: Goodyear G182 RSD 11R22.5 16PR. 42.1 in. diameter, all position. 19.6 in. SLR. Code is priced per pair of tires.	64
4900004	O	Rear Tire Quantity: 4	0
5042367	O	Front Wheel: Accuride 29300 22.5x9 steel Steel Armor[TM] powder coat, hub-pilot mount. 10000lb. maximum rating. 5-hand holes. Not air disc brake compatible.	79
5045254	U	FR WHL:ALCOA 89465 22.5X9 AL	-18
5242251	O	Rear Wheel: Accuride 29001 22.5x7.5 steel Steel Armor[TM] powder coat, hub-pilot mount. 6610 lb. maximum rating. Code is priced per pair of wheels.	18
5853906	O	Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	0
5900004	O	Rear Wheel/Rim Quantity: 4	0
Frame & Equipment			
6056200	O	Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel to 284 in. Truck frame weight is 3,48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	145
6308715	O	Bumper: Aerodynamic Chrome Requires a bumper setting code.	0
6319409	S	40.9 in. Bumper setting. Requires a bumper code.	0
6321005	O	Removable Front Tow Hooks: 2.	15
6390103	S	Front mudflaps.	0
6400634	O	Battery box cantilever aluminum BOC with smooth aluminum cover.	2
6409902	O	Battery box location: RH Side.	15

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/5/2019 11:01:32 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q70120068
Prepared by:	Administrator		Version Number:	41.20



Data	Code	Description	Weight
6451059	O	T270/370 Non-polished 2010 or later DPF/SCR cover with cab access step assembly, RH under. End plates will be painted standard black frame color.	0
6490124	O	Five-piece bolted crossmember assembly with 16mm frame fasteners, center and rear frame.	-32
6490427	O	Aluminum underbell crossmember. Only with non-drive front axle 16K and greater. For T370 only.	19
6490430	O	Bolted Rear Cab Support Crossmember. Replaces T3 standard.	17
6679813	U	2013 EPA Emissions Diesel or Gas Engine	0
6741023	O	Square end-of-frame w/ bolted crossmember, non-towing.	41
Fuel Tanks & Equip			
7210056	O	Fuel Tank: 56 US gallon 24.5in. aluminum under replace.	-45
7722011	O	Small round DEF tank. 11 gallons of usable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
7889203	O	Standard DEF to fuel fill ratio: 2:1 or greater.	0
7889604	O	DEF tank location is on the LH.	0
7920056	O	Location: 56 gal fuel tank LH under cab	0
Cab & Equipment			
8024310	S	Cab: Curved Glass Conventional. Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.	0
8090310	S	Hood: Sloped aerodynamic hood includes grill & separate bumper.	0
8108010	S	Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
8201200	O	Adjustable telescoping tilt steering column.	10
8202996	O	Manual override switch: For fan hub, w/o warning lamp. For fire truck pumpers only. Option used to request fan on only. The engine may turn fan on and off on regardless of switch.	1
8208496	O	Three spare switches: Wired to power.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/5/2019 11:01:32 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q70120068
Prepared by:	Administrator		Version Number:	41.20



Data	Code	Description	Weight
8220106	O	Gauge: Dash mounted air filter restriction gauge.	0
8282009	S	Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
8330003	S	Cab interior: Pinnacle. Includes vinyl headliner & cab back panel, slate gray interior, dark slate gray seats, floormats, LH/RH inside sunvisor & door courtesy lights.	0
8410092	O	Driver seat: Kenworth Air cushion Premium Plus HB cloth. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6-58 degree recline, air suspension w/ cover, dual armrests, and triple chamber air lumbar support. Cushion and back include air adjustment. Seat cushion is 20 inches wide w/ 2-position tilt and 6-position front cushion support. Seat material has a horizontal stitch pattern and is 2-tone in color. Standard storage includes a side bolster pocket and a hanging pocket. Seat back is carpeted, and high back seats include a storage pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
8480080	S	Rider Seat: Kenworth Toolbox Plus IB cloth. Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
8601421	O	Kenworth Radio with AM/FM/WB/USB and Bluetooth	4
8700083	O	Under-dash center console: W/2 cup holders, 1 ashtray, 1 lighter, 1 12V outlet & a storage compartment.	0
8700154	O	Self cancelling turn signal: W/head light dimmer switch.	0
8800200	S	Cab access contoured grabhandles, LH/RH.	0
8832115	O	Daylite Door: LH/RH includes RH peeper window	0
8841411	O	Single air horn under cab.	3
8850300	S	Look-Down, Pass. Door, Stainless 8.5x4.4	0
8850817	O	Mirror: Dual Fender Mounted, Round Convex	8
8865001	O	Mirror: Dual Kenworth aerodynamic heated motorized 7 in. x 13 in. mirror w/ chrome shell. LH/RH convex mirrors 5 in. x 7 in. heated. Mirror brackets set for 8 1/2 ft load width. Switch located on door pad.	26
8879213	O	Electric-powered LH & RH door window lifts. Switch located on door.	0
8879911	O	Two corner & one rear cab stationary windows 17.5 in. x 16 in. (two) & 17 in. x 36 in. (one).	24

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/5/2019 11:01:32 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q70120068
Prepared by:	Administrator		Version Number:	41.20



Data	Code	Description	Weight
Lights & Instruments			
9010801	S	Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0
9022137	O	Marker Lights: Five, rectangular, LED	0
9030010	S	Turn Signal Lights: Mounted on fender	0
9070138	S	Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
9090000	O	Daytime Running Lamps.	0
9090151	O	Wiring:Cust. Install Trlr Elec. Brake Controller. Class 8/T4 Content Includes Dash Signals: Ignition Power (20A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To EOF Junction Box. These Signals Are Located Near The NavPlus HD Area. No Need To Code For An Additional End of Frame Junction Box. EOF Junction Box Signals Are: Ground, Tail Lamp, Marker Lamp, Left Turn, Right Turn, Stop Lamp and Electric Trailer Brake Controller Wired To Dash. Medium Duty (not T4) Content Includes A MP 280 Series Connector In Dash Near Driver Door Connections With Signals: Battery Power (40A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To Chassis Connector. Medium Duty (not T4) 2 Way Deutsch Chassis Connector Located Near Back of Cab, With Signals: Ground and Electric Trailer Brake Controller Wired To Dash Connector.	1
9090845	O	Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0
Air Equipment			
9101023	O	Air dryer: Bendix AD-SP heated. With 2010 engine installations the dryer is mounted under the hood.	0
9108001	O	Moisture ejection valve w/ pull cable drain.	0
Extended Warranty			
9200008	O	Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0
9200022	S	Base Warranty - Standard Service Medium Duty 12 months / Unlimited miles & km	0
Miscellaneous			
9400072	O	Ship to Dealer.	0
9409852	O	GHG Secondary Manufacturer: Does Not Apply	0
Paint			
9700000	O	Paint color number(s). N97020 A - L6980 KELLY GREEN N97200 FRAME N0001 BLACK	0
9943004	O	Bumper Unpainted	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 3/5/2019 11:01:32 AM
Effective Date: Jan 1, 2018
Prepared by: Administrator

Complete

Model Number: T370 SERIES CONVENTIONAL
Quote/DTPO/CO: Q70120068
Version Number: 41.20



Data	Code	Description	Weight
9943052	O	Day Cab Pearl Metallic Paint	0
9944820	O	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0
Total Weight			12238 lb

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	3/5/2019 11:01:32 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q70120068
Prepared by:	Administrator		Version Number:	41.20